

Tepelub 122

Lubricant

Tepelub 122 ;

- Very effective External lubricant
- Compatible PVC and all PVC additives
- Regulates the melt flow and prevents melt stickiness.
- Very suitable for transparent products
- Imparts very smooth and shiny finish to the product

PROPERTIES

Appearance	: White, Flake or powder
Melting point	: 100°C-110 °C
Flash Point	: 300°C
Storage Stability	: 2 years under cool and dry storage conditions in orginally packing
Packing	: 20-25 Paper, PP, or PE bag kg net
Dosage :	0,5 – 2 phr

Tepe Kimya (M) SDN. BHD.

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848

Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.

Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla İstanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.

63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435

Email: info@tepekimya.com