

# Lubricant TP 155

## Lubricant

LUBRICANT TP 155 ;

- Very effective internal and external lubricant
- Compatible PVC and all PVC additives
- Regulates the melt flow and prevents melt stickiness.
- Very suitable for transparent products
- Imparts very smooth and shiny finish to the product
- Regulates the viscosities of PVC plastisols

## PROPERTIES

Chemical Characteristics : Ester of unsaturated fatty acids

Appearance : Light yellow transparent liquid

Solidification Point : Below 7 ° C

Storage Stability : 2 years under cool and dry storage conditions in originally packing

Packing : Drums containing 175 kg net

Dosage : 0,5 – 2 phr

***This Product has a ROHS Certificate***

### **Tepe Kimya (M) SDN. BHD.**

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9  
81700 Pasir Gudang Johor MALAYSIA  
Tel: +60 7 251 7844 Fax: +60 7 251 7848

**Web:** [www.tepekimya.com](http://www.tepekimya.com)

### **Tepe Kimya San. ve Tic.Ltd.Şti.**

Kimyacılar Organize Sanayi Bölgesi  
Melek Aras Bulvarı N:12 34959  
Tepeören Tuzla İstanbul/TURKEY  
Tel:+90 216 5931920 Fax:+90 216 5931925

### **Tepe Trade Intl. Chem Pte. Ltd.**

63 Mount Sinai Drive #05-01  
277116 SINGAPORE  
Tel:+65 932 65813 Fax: +65 631 48 435

**Email:** [info@tepekimya.com](mailto:info@tepekimya.com)