

PROCESSING AID PY-30

PVC Processing Aid

Application of PY-30 improve melt homogeneity, achieving a perfect surface finish of the final product, increases melt strength and fusion time significantly. It has the capability to bind PVC chains together, resulting increased melt elasticity by having long polymer chains. PY-30 provides perfect wall thickness when use with Ca-30

PROPERTIES

FORM	: Powder
COLOUR	: White
BULK DENSITY (g/cc)	: 0.55 ± 0.1
MOISTURE %	:1.0 max.
VISCOSITY (CST)	:13,0-16,5

APPLICATION

- Pressure Pipe
- Big diameter pipe
- Injection mouldings
- PVC foam applications
- Extrusion processes
- Rigid PVC processes

RECOMMENDED CHARGES

Usually 0.5 - 7.0 phr depending on the processing conditions and the type of the materials to be produced.

PACKING: 25 kg net PP bags

Tepe Kimya (M) SDN. BHD.

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848

Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.

Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.

63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435

Email: info@tepekimya.com