

# Tepelub 120

## *Lubricant*

### **Tepelub 120 ;**

- Very effective external lubricant
- Compatible PVC and all PVC additives
- Very suitable for transparent products
- Imparts very smooth and shiny finish to the product

### **PROPERTIES**

Appearance	: Flakes
Iodine Value	: 0.5 max
Acid Value	: 206 - 212
Saponification Value	: 207 -213
Titer	: 54-56
Colour Lovibond	: Red 0.3 max Yellow 1.5 max
Storage Stability	: 2 years under cool and dry storage conditions in originally packing
Packing	: 25 kg net Paper, PP, or PE bag
Dosage	: 0,5 – 2 phr

#### **Tepe Kimya (M) SDN. BHD.**

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9  
81700 Pasir Gudang Johor MALAYSIA  
Tel: +60 7 251 7844 Fax: +60 7 251 7848

**Web:** [www.tepekimya.com](http://www.tepekimya.com)

#### **Tepe Kimya San. ve Tic.Ltd.Şti.**

Kimyacılar Organize Sanayi Bölgesi  
Melek Aras Bulvarı N:12 34959  
Tepeören Tuzla İstanbul/TURKEY  
Tel:+90 216 5931920 Fax:+90 216 5931925

#### **Tepe Trade Intl. Chem Pte. Ltd.**

63 Mount Sinai Drive #05-01  
277116 SINGAPORE  
Tel:+65 932 65813 Fax: +65 631 48 435

**Email:** [info@tepekimya.com](mailto:info@tepekimya.com)