

KRESBY TP 316 FL

Process Aid

KRESBY TP 316 FL used as dispersing agent in order to obtain better dispersion Of fillers, especially Calcium Carbonate, pigment and carbon blacks.

KRESBY TP 316 FL improve the rubber or plastic compound flow of all kinds of plastic compounds which are calendered, extruded or used for transfer and mouldings.

KRESBY TP 316 FL improves the surface finish.

KRESBY TP 316 FL compatible all kind of Plastic PE, PP, ABS, PS,... etc and all rubber NR, SBR, EPDM, CR, NBR, IIR, CSM, BR, EVA, ECO, CM.

PROPERTIES

Chemical Characteristics : Combination of fatty acid derivatives and metal soap

Appearance : White Flakes

Melting Point : 90 ± 5

Ash content : $12 \% \pm 1$

Storage Stability : 3 years under cool and dry storage conditions in originally packing

Packing : Paper bags containing 20 kg net

Dosage : 2 – 4 phr

Tepe Kimya (M) SDN. BHD.

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.

Kimyaçılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla İstanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.

63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
Email: info@tepekimya.com